



## Specification

Range	0...10MPa to 0...150MPa
Output	Contact switch signal
Accuracy	±1.6%FS
Input Voltage	24VDC (12~36)VDC; 200VAC ;380VAC
Configuration	Bourdon tube
Over Pressure	1.5xFS
Max Diaphragm Temperature	350°C
Dial Diameter	100mm
Flexible Length	0.5...5M
Electric connector	Direct cable
Process connector	M22*1.5 , G3/4 (customer tailor)
Electric connector	5 pins , DIN , gland leading
Wiring diaphragm	Red / yellow for NO ; Red/blue for NC

## Installation Dimension

<p>Planar Sealed</p>	D1	M22×1.5	M28×1.5	G3/4"	PT3/8"
	D2	Φ 16.1	Φ 18.3	Φ 18.3	Φ 10.3
	D3	Φ 20.1	Φ 26.1	Φ 24.2	Φ 14.9
	M	Φ 23	Φ 30	Φ 21	Φ 11
	A	11	12	12	14
	B	12	15	15	19
	C	40	35	35	40
	<p>45° Slope Sealed</p>	D1	M12×1.5	M14×1.5	1/2-20UNF
D2		Φ 8	Φ 8	Φ 8	Φ 10.1
D3		Φ 10.8	Φ 12.5	Φ 11.5	Φ 16.1
D4		Φ 12.5	Φ 14.5	Φ 13.1	Φ 20
A		6	6	6	6.5
B		9	9.5	9.5	10

## Ordering Guide

Model	Range	Output	Snout&Flexible Length	Process connection	Other requirement
PT124Y-616	---	---	---	---	---

Example: PT124Y-616-350Bar-6"/18"- M22\*1.5

## Shanghai Zhaohui Pressure Apparatus Co.,Ltd

5-6F No.8 Building No.115 ,Lane 1276 Nanle Road,  
 Songjiang District Shanghai 201600 China  
 Tel:+86-21-51691919 67755189 Fax:+86-21-67755185  
 E-mail: info@zhyqsensor.com  
 www.zhyqsensor.com

